



SAXON CLW 218

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor,

Kährs Luxury Tiles Click floor Saxon has dark and deep shades of brown and grey, combined with detailed grain definition, knots and cracks, creating a characterful yet elegant floor.

PRODUCT DETAILS		FACTS
Article Number	LTCLW2109-218	Design
Dimensions	218 x 1210 mm	Range
Weight per Package	20.6 kg	Collection
Area per Package	2.1 m ²	Joint
Area per pallet	84.5 m ²	Floor heating
Construction	Click 6 mm	Backside material
DETAIL DESCRIPTION		Thickness

Design	Wood design
Range	Luxury Tiles
Collection	Nature Collection
Joint	Click5G
Floor heating	Yes
Backside material	IXPE Sound reducing backing
Thickness	6 mm
Installation method	Floating

ECHNICAL PROPE	RTIES		
Application	EN ISO 10874	23/33/42	
Effect of furniture leg	EN ISO 16581	No visible damage/Change	
Emission of formaldehyde		E1	
Reaction To Fire	EN13501- 1	Bfl-s1	B _{rr} 21
Formaldehyde Emission	EN717-1	E1	
Thermal Resista Value	ance R-	0.035 (m2K/W)	
Residual indent	ation EN	< 0.2 mm (*with underlayment)	
Dimensional stability	EN ISO 23999	< 0.1 %	KN
Colour fastness	EN ISO 105-B02	≥ 6	3 2
Slip resistance	EN 13893	DS (>0.3)	97.5g
Slip resistance	DIN 51130	R10	96 05

Descriptions & Imagery

ideal for renovation projects.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









TECHNICAL PROPERTIES

I LCI INICAL FROF	LIKTILO		
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	7
Scratch resistance	EN16094	Pass with good results	
Chemical resistance	EN ISO 26987	Pass with good results	₹ ○
Effect of castor chair	EN 425	Suitable	a
Resistance to ba fungi	cteria and	Good	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	<u></u>
Commercial usage classification	EN 14354:2017	Class 33	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









Other products in this collection



Aspen - Click 6 mm



Sapo - Click 6 mm



Saxon - Click 6 mm



Redwood - Click 6 mm



Sarek - Click 6 mm



Oulanka - Click 6 mm



Taiga - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









