



TAIGA CLW 218

Kährs Rigid Click Luxury Tiles floor Taiga is characterized by warm, brown tones and grey highlights, a floor that effortlessly creates a homely feeling in any space. Natural features including knots and cracks emphasize the authentic look of this floor.

PRODUCT DETAILS

Article Number	LTCLW2115-218
Dimensions	218 x 1210 mm
Weight per Package	20.6 kg
Area per Package	2.1 m ²
Area per pallet	84.5 m ²
	Click 6 mm

DETAIL DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

FACTS

Design	Wood design
Range	Luxury Tiles
Collection	Nature Collection
Joint	Click5G
Floor heating	Yes
Backside material	IXPE Sound reducing backing
	6 mm
Installation method	Floating

TECHNICAL PROPERTIES




Application	EN ISO 23/33/42	10874	
Emission of formaldehyde	E1		
Reaction To Fire	EN13501-	Bfl-s1	
Formaldehyde Emission	EN717-1	E1	
Thermal Resistance R-Value	0.035 (m2K/W)		
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	
Slip resistance	EN 13893	DS (>0.3)	
Slip resistance	DIN 51130	R10	
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



TECHNICAL PROPERTIES

Scratch resistance	EN16094	Pass with good results	
Chemical resistance	EN ISO 26987	Pass with good results	
Resistance to bacteria and fungi		Good	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	
Commercial usage classification	EN 14354:2017	Class 33	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Aspen - Click 6 mm



Sapo - Click 6 mm



Saxon - Click 6 mm



Redwood - Click 6 mm



Sarek - Click 6 mm



Oulanka - Click 6 mm



Taiga - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

