

OAK MAGGIORE

The black-and-tan colour range in this single-strip floor from the Da Capo Collection results in an extremely rustic expression. The naturally occurring knots and cracks add to the quality of the surface, giving the floor a worn complexion reminiscent of reclaimed timber. Each board is carefully brushed to bring out the quality of the grain and highlight the natural properties of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the aged appearance of the floor.

| Wood Floors / 3-layer parquet | | | |
|--|---|---|--|
| | Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| 151YDDEKF0KW195 / 7393969305914 | range | | |
| Plank / Oak | Warranty | 30 years | |
| Oil / Stained | TECHNICAL PROPERTIES | | |
| | | | 7%±2% |
| Handscraped, Bevelled 4-sided, Brushed | | LINISIOS | |
| 190 x 1900 x 15 mm | 5 | | >500 kg/m³ |
| 19 kg / 8.64 kg | Reaction To Fire | EN13501-1 | Dfl-s1 |
| | – Formaldehvde Emission | FN717-1 | E1 |
| 2.17 m ² / 75.95 m ² | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| | Breaking Strength N/mm ² | EN1533 | NPD |
| Expressive | | | 0,11W/mK |
| Woodloc® 5G | , | | Class 1 |
| Glue-down, Floating | , | LNJJU-Z | |
| Yes | | | Compliant |
| Hardwood / 3.5 mm | - Slip resistance | CEN/1515676 | NPD |
| | PRESIDE DAVE LAN HTTPERF | | |
| 2-4 times | | | |
| Pine/Spruce | Compliant Street OW | DAJIA | |
| Veneer | _ | | |
| | Plank / Oak Oil / Stained Handscraped, Bevelled 4-sided, Brushed 190 x 1900 x 15 mm 19 kg / 8.64 kg 2.17 m ² / 75.95 m ² Expressive Woodloc® 5G Glue-down, Floating Yes Hardwood / 3.5 mm 2-4 times Pine/Spruce | Plank / OakWarrantyOil / StainedTECHNICAL PROPERTIESHandscraped, Bevelled 4-sided, BrushedMoisture content190 x 1900 x 15 mmMinimun Mean Density19 kg / 8.64 kgReaction To Fire2.17 m² / 75.95 m²Formaldehyde Emission2.17 m² / 75.95 m²Content PCPExpressiveBreaking Strength N/mm²Woodloc® 5GBiological DurabilityGlue-down, FloatingCARB2YesSlip resistanceHardwood / 3.5 mmSip resistance2-4 timesFine/Spruce | Plank / OakWarranty30 yearsOil / StainedTECHNICAL PROPERTIESMoisture contentEN13183Handscraped, Bevelled 4-sided, BrushedMinimun Mean Density kg/m³EN13501-119 kg / 8.64 kgReaction To FireEN13501-12.17 m² / 75.95 m²Content PCPCEN/TR14823ExpressiveBreaking Strength N/mm²EN1533Yoodloc@ 5GBiological DurabilityEN12664Glue-down, FloatingSlip resistanceCEN/TS15676YesSlip resistanceCEN/TS15676Hardwood / 3.5 mmSip resistanceCEN/TS156762-4 timesPine/SpruceESCACEN/TS15676 |

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection





OAK DECORUM

OAK SPARUTO





OAK DOMO





OAK INDOSSATI



OAK DUSSATO



OAK MAGGIORE

OAK UNICO