

## OAK SAND

Oak Sand is a beautiful and warm yet light and lively oak floor, reminiscent of warm, sandy beaches. It is a 3-strip, matt lacquered floor with lots of character. Oak Sand is ideal for any interiors, creating a light and homely feeling.

PRODUCT DETAILS
LRV / LRV Std1

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	133N22EK1KKW240 / 7393969306362
Design / Wood Species	3-strip / Oak
Surface Treatment /	Matt lacquer / Stained
Natural/Stained	
Width x Length x Thickness	200 x 2423 x 13 mm
Weight per package / per	24 kg / 7.2 kg
m2	
Area per package / per	3.4 m <sup>2</sup> / 170 m <sup>2</sup>
pallet	
Grading	Lively
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 2.6 mm
thickness	
Resandable	2 times
Core material	Pine/Spruce
Backside material	Spruce
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	

Warranty	20 years	
TECHNICAL PROPERT	IES	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Poaction To Fire	ENI12501 1	Dfl c1

40 / 4

moistare correctie	21110100	7.02270
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









## DETAILED DESCRIPTION

Colour change: Stained product - noticeable colour change over time.

Packages may contain start and stop boards.

## Other products in this collection









OAK CLAY

ASH CORAL

OAK SAND

OAK SEED



OAK CHALK