



OAK CONCRETE

A rustic, handscraped product. Grey stain and nature oil.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	151YCDEKFMKW195 / 7393969305877	
Design / Wood Species	1-strip / Oak	
Surface Treatment /	Oil / Stained	
Natural/Stained		
Refining Treatment	Handscraped, Brushed, Bevelled 4-sided	
Width x Length x Thickness	190 x 1900 x 15 mm	
Weight per package / per	17 kg / 7.73 kg	
m2		
Area per package / per	2.17 m ² / 75.95 m ²	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5G	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-3 times	
Core material	Pine/Spruce	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

PRODUCT DETAILS

Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection







OAK CONCRETE



OAK STRAW



OAK OYSTER







OAK CAMINO