

WENTWOOD DBW 229 - 0.7 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to elegant herringbone and rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.7 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
n Luxury Vinyl Tiles and Planks / Dry Back LVT		Statical electrical	EN 1815	< 2 kV (antistatic)
Article Number / EAN Code LTDBW2007-229 / 7393969110495		propensity		
Tile Design		Chemical resistance	EN ISO 26987	Pass with good results
228.6 x 1219.2 x 2.5 mm		Resistance to bacteria and		Good
16.4 kg / 4.21 kg		fungi		
		SION C/	THAI ISO BAR	
3.9 m² / 265.2 m²		tloor C		
		A BALEW ONION OF COMMENTARY	FREE	
Glue-down				
Yes				
0.7 mm		_		
EN13501-1	Bfl-s1			
	0.011 (m2K/W)			
EN ISO 23999	< 0.1 %	_		
EN ISO 105-B02	≥ 6	_		
EN 13893	DS (>0.3)			
DIN 51130	R10			
	LTDBW2007-229 / 73 Tile Design 228.6 x 1219.2 x 2.5 16.4 kg / 4.21 kg 3.9 m² / 265.2 m² Glue-down Yes 0.7 mm EN13501-1 EN 150 23999 EN 150 105-B02 EN 13893	LTDBW2007-229 / 7393969110495 Tile Design 228.6 x 1219.2 x 2.5 mm 16.4 kg / 4.21 kg 3.9 m² / 265.2 m² Glue-down Yes 0.7 mm EN13501-1 Bfl-s1 0.011 (m2K/W) EN ISO 23999 <0.1 % EN ISO 105-B02 ≥6 EN 13893 DS (>0.3)	Luxury Vinyl Tiles and Planks / Dry Back LVT Statical electrical propensity LTDBW2007-229 / 7393969110495 propensity Tile Design Chemical resistance 228.6 x 1219.2 x 2.5 mm Resistance to bacteria au fungi 16.4 kg / 4.21 kg fungi 3.9 m² / 265.2 m² Image: Compare the second seco	Luxury Vinyl Tiles and Planks / Dry Back LVT Statical electrical propensity EN 1815 LTDBW2007-229 / 7393969110495 propensity EN ISO 26987 Tile Design Chemical resistance EN ISO 26987 228.6 x 1219.2 x 2.5 mm Resistance to bacteria and fungi 16.4 kg / 4.21 kg fungi Esistance to bacteria and 3.9 m² / 265.2 m² fungi Esistance to bacteria and Glue-down Fesion Esistance Yes 0.7 mm O.011 (m2K/W) EN 150 23999 < 0.1 %

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kahrs (UK) Ltd | www.kahrs.com | [©]Kährs, United Kingdom & Ireland 2025-05-12

Other products in this collection

