



## **OAK SPARUTO**

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Foursided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

PRODUCT DETAILS		PRODU
Product type / Construction	Wood Floors / 3-layer parquet	Hardne
Article Number / EAN Code	151YDDEKFRKW195 / 7393969305938	range
Design / Wood Species	Plank / Oak	Warrant
Surface treatment /	Oil / Natural	TECHN
Natural/Stained		— Moistur
Design features	Bevelled 4-sided, Brushed, Smoked,	Minimu
	Handscraped, Wooden plugs	kg/m³
Width x Length x Thickness	190 x 1900 x 15 mm	Reaction
Weight per package / per	19 kg / 8.64 kg	
m2		Formalo
Area per package / per	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>	— Content
pallet		Breakin
Grading	Expressive	— Therma
Joint	Woodloc® 5G	Biologic
Installation method	Floating, Glue-down	CARB2
Floor heating	Yes	Slip resi
Wear leayer material /	Hardwood / 3.5 mm	(TSCA
thickness		CARB P
Resandable	2-4 times	Complian
Core material	Pine/Spruce	
Backside material	Veneer	

PRODUCT	DETAILS
---------	---------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

www.kahrs.com | ©Kährs

## Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE