



OAK SPARUTO

PRODUCT DETAILS

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Foursided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

PRODUCT DETAILS		PRODU
Product type / Construction	Wood Floors / 3-layer parquet	Hardnes
Article Number / EAN Code	151YDDEKFRKW195 / 7393969305938	range
Design / Wood Species	1-strip / Oak	Warrant
Surface treatment /	Oil / Natural	TECHN
Natural/Stained		— Moistur
Design features	Bevelled 4-sided, Brushed, Smoked,	-
	Handscraped, Wooden plugs	Minimuı —— kg/m³
Width x Length x Thickness	190 x 1900 x 15 mm	— Reaction
Weight per package / per	19 kg / 8.64 kg	Formalo
m2		
Area per package / per	2.17 m ² / 75.95 m ²	Content
pallet		Breaking
Grading	Expressive	Therma
Joint	Woodloc® 5G	Therma
Installation method	Floating, Glue-down	Biologic
Floor heating	Yes	CARB2
Wear leayer material /	Hardwood / 3.5 mm	Slip resi
thickness		TSCA
Resandable	2-4 times	CARB P
Core material	Pine/Spruce lamella	Compliant
Backside material	Veneer	

PROD	UCT	DETA	ILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE