



## **OAK SPARUTO**

The burnt caramel hues found in this single-strip floor from the Da Capo Collection are enhanced by the rich smoked effect on the boards resulting in a luxurious colour palette. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative square joints add to its crafted appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Foursided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn complexion of the floor.

	PRODUCT DETAILS			
Wood Floors / 3-layer parquet	Hardness (Brinell) value /			
151YDDEKFRKW195 / 7393969305938	range			
Plank / Oak	Warranty			
Oil / Natural	TECHNICAL PROPERTIE			
	Moisture content			
Bevelled 4-sided, Brushed, Smoked,	Minimun Mean Density			
Handscraped, Wooden plugs	kg/m <sup>3</sup>			
190 x 1900 x 15 mm	— Reaction To Fire			
19 kg / 8.64 kg	Formaldehyde Emission			
	— Content PCP			
2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>	Breaking Strength N/mm <sup>2</sup>			
Expressive	Thermal Conductivity			
Woodloc® 5G	Biological Durability			
Floating, Glue-down	CARB2			
Yes	Slip resistance			
Hardwood / 3.5 mm	TSCA SMILION LAW HT SELFT			
	CARB P2			
2-4 times	Compliant			
Pine/Spruce	<del></del>			
Veneer				
	151YDDEKFRKW195 / 7393969305938 Plank / Oak Oil / Natural  Bevelled 4-sided, Brushed, Smoked, Handscraped, Wooden plugs 190 x 1900 x 15 mm 19 kg / 8.64 kg  2.17 m² / 75.95 m²  Expressive Woodloc® 5G Floating, Glue-down Yes Hardwood / 3.5 mm  2-4 times Pine/Spruce			

P	R	0	D	U	C	Γ	D	E-	Γ	٩I	L	S	

Hardness (Brinell) value /	3,7 / 2.2 - 5.9				
range					
Warranty	30 years				
TECHNICAL PROPERTIES	5				
Moisture content	EN13183	7%±2%			
Minimun Mean Density		>500 kg/m³			
kg/m³					
Reaction To Fire	EN13501-1	Dfl-s1			
Formaldehyde Emission	EN717-1	E1			
Content PCP	CEN/TR14823	≤ 5 ppm			
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD			
Thermal Conductivity	EN12664	0,11W/mK			
Biological Durability	EN350-2	Class 1			
CARB2		Compliant			
Slip resistance	CEN/TS15676	NPD			



## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

## Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE