



OAK CAMINO

A very rustic product with a heavy handscraping. Natural oil

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	151YDDEKFZKW195 / 7393969305891
Design / Wood Species	1-strip / Oak
Surface Treatment /	Oil / Natural
Natural/Stained	
Refining Treatment	Bevelled 4-sided, Brushed, Handscraped
Width x Length x Thickness	190 x 1900 x 15 mm
Weight per package / per	17 kg / 7.73 kg
m2	
Area per package / per	2.17 m ² / 75.95 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Resistance R-Value	!	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





DETAILED DESCRIPTION

thickness Resandable

Warranty

Core material

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

2-3 times

30 years

Pine/Spruce lamella

Packages may contain start and stop boards.

Other products in this collection







OAK CONCRETE



OAK STRAW



OAK OYSTER







OAK CAMINO