



## OAK FARTH

The smoked finish on this single-strip oak floor from the Artisan Collection enhances the natural colour variations for a rustic expression. Knots and cracks pepper the boards, adding depth and balancing the toasted sesame seed highlights. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS			
Product type / Construction	Wood Flooring / 3-layer parquet		
Article Number / EAN Code	151YCDEKFCKW195 / 7393969305860		
Design / Wood Species	1-strip / Oak		
Surface Treatment /	Oil / Natural		
Natural/Stained			
Refining Treatment	Bevelled 4-sided, Brushed, Smoked,		
	Handscraped		
Width x Length x Thickness	190 x 1900 x 15 mm		
Weight per package / per	17 kg / 7.83 kg		
m2			
Area per package / per	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>		
pallet			
Grading	Dynamic		
Joint	Woodloc® 5G		
Installation method	Floating, Glue-down		
Floor heating	Yes		
Wear leayer material /	Hardwood / 3.5 mm		
thickness			
Resandable	2-3 times		
Core material	Pine/Spruce		
Backside material	Veneer		

PRODUCT I	DETAILS
-----------	---------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m <sup>3</sup>
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





## **DETAILED DESCRIPTION**

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: The smoked finish accentuates the natural colour variations, creating a stronger contrast between light and dark tones initially. Over time, the colour variations will soften, resulting in a more uniform overall appearance. The oiled surface will develop a natural patina.

Packages may contain start and stop boards.

## **Descriptions & Imagery**

Kahrs (UK) Ltd | www.kahrs.com | ©Kährs, United Kingdom & Ireland 2025-09-06

## Other products in this collection







OAK CONCRETE



OAK STRAW



OAK OYSTER







OAK CAMINO