



BLAIKEN DRY BACK 0.7 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to elegant herringbone and rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.7 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			-
Product type / Construction	Vinyl Flooring / Dry Back LVT		
Article Number / EAN Code	LTDBW2303-102 / 7393969306638		
Design	Herringbone		
Width x Length x Thickness	4 x 18 x 1/8"		_ [
Weight per package / per	25.8 lbs / 9.2 lbs		_ i
m2			1
Area per package / per	29.9 sqft / 2632.9 sqft		
pallet			
Installation method	Glue-Down		
Floor heating	Yes		
Wear leayer thickness	0"		
TECHNICAL PROPERTIES			
Reaction To Fire	EN13501-1	Bfl-s1	
Thermal Resistance R-Value		0.011 (m2K/W)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	

EN 13893

DIN 51130



Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		











Slip resistance

Slip resistance

DS (>0.3)

R10

Other products in this collection

