

OAK GLOW

This 2-strip oak floor from the Lumen Collection features saturated earth tones highlighted by a rich smoke finish, which accentuates the naturally occurring blemishes in the timber. Each board is carefully brushed to perfection, bringing out the darker nuances in the grain for a timeless, rustic expression. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DETAILS | | PRODUCT DETAILS | | |
|-----------------------------|---|-------------------------------------|-----------------|-----------------------------|
| Product type / Construction | Wood Floors / 3-layer parquet | Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| Article Number / EAN Code | 152N6BEKF4KW240 / 7393969046305 | range | | |
| Design / Wood Species | 2-strip / Oak | LRV / LRV Std1 | 13 / 3.7 | |
| Surface treatment / | Ultra matt lacquer / Stained | Warranty | 30 years | |
| Natural/Stained | | | | |
| Design features | Brushed, Smoked | — Moisture content | EN13183 | 7%±2% |
| Width x Length x Thickness | 200 x 2423 x 15 mm | — Minimun Mean Density | ENISIOS | >500 kg/m ³ |
| Weight per package / per | 23 kg / 7.9 kg | kg/m ³ | | ~500 kg/11 |
| m2 | | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Area per package / per | 2.91 m ² / 130.95 m ² | Formaldehyde Emission | EN717-1 | E1 |
| pallet | | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Grading | Lively | Breaking Strength N/mm ² | EN1533 | NPD |
| Joint | Woodloc® 5S | — Thermal Conductivity | EN12664 | 0,11W/mK |
| Installation method | Floating, Glue-down | | EN350-2 | Class 1 |
| Floor heating | Yes | | 2110000 2 | Compliant |
| Wear leayer material / | Hardwood / 3.5 mm | Slip resistance | CEN/TS15676 | NPD |
| thickness | | | CEN/1515070 | NI D |
| Resandable | 2-3 times | | anssion clarge | SPESSIONS GAVE LIVE PTERSUP |
| Core material | Pine/Spruce/Alder | CARB P2 | | |
| Backside material | Spruce | Compliant SundaH | us BASIA | |
| | | floor score (F | | |

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. The smoked design enhances the natural colour variations and creates a stronger contrast between light and dark.

O SEA BILL

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Smoked product - noticeable color change, some muting of colour variations over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection

















OAK RIME



OAK TWILIGHT



OAK DUSK

OAK MIST

OAK ECLIPSE

OAK DAWN