

OAK INDOSSATI CONSUMER SAMPLE

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer parquet
Article Number	SA01-151YDDEKFKHW
Design / Wood Species	1-strip / Oak
Surface Treatment / Natural/Stained	Oil / Stained
Refining Treatment	Bevelled 4-sided, Brushed, Light smoked, Handscraped
Width x Length x Thickness	190 x 200 x 15 mm

Grading	Expressive
Joint	Woodloc® 5G
Installation method	Glue-down, Floating
Floor heating	Yes
Wear layer material / thickness	Hardwood / 3.5 mm
Core material	Pine/Spruce
Backside material	Veneer
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
Warranty	30 years

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.


Packages may contain start and stop boards.

Descriptions & Imagery


All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |
www.kahrs.com | ©Kährs,
United Kingdom & Ireland
2026-05-10

Other products in this collection



OAK DECORUM




OAK DOMO




OAK DUSSATO



OAK UNICO



OAK SPARUTO



OAK INDOSSATI



OAK MAGGIORE