



TONGASS DBW 102

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to elegant herringbone and rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.7 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS

| Luxury Vinyl Tiles / Dry Back Herringbone | | (|
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LTDBW2006-102 / 7393969110778 | | |
| Wood herringbone design | | f |
| 102 x 457 x 2.5 mm | | |
| 11.7 kg / 4.18 kg | | |
| | | |
| 2.8 m ² / 244.6 m ² | | |
| | | |
| Glue-down | | |
| 0.7 mm | | |
| | | |
| EN13501-1 | Bfl-s1 | |
| | 0.011 (m2K/W) | |
| EN ISO 23999 | < 0.1 % | |
| EN ISO 105-B02 | ≥ 6 | |
| EN 13893 | DS (>0.3) | |
| DIN 51130 | R10 | |
| | LTDBW2006-102 / 7 Wood herringbone of 102 x 457 x 2.5 mm 11.7 kg / 4.18 kg 2.8 m² / 244.6 m² Glue-down 0.7 mm EN13501-1 EN ISO 23999 EN ISO 105-B02 EN 13893 | LTDBW2006-102 / 7393969110778 Wood herringbone design 102 x 457 x 2.5 mm 11.7 kg / 4.18 kg 2.8 m² / 244.6 m² Glue-down 0.7 mm EN13501-1 Bfl-s1 0.011 (m2K/W) EN ISO 23999 < 0.1 % EN ISO 105-B02 ≥ 6 EN 13893 DS (>0.3) |

TECHNICAL PROPERTIES

| Chemical resistance | EN ISO 26987 | Pass with good results |
|----------------------------|--------------|------------------------|
| Resistance to bacteria and | | Good |
| - fungi | | |











Statical electrical propensity EN 1815

< 2 kV (antistatic)

Other products in this collection

