



## CHEVRON DARK BROWN

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three strips in a row between a left & right board. Chevron Dark Brown is a dark, strong brown floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil.

### PRODUCT DETAILS

|                    |   |
|--------------------|---|
| Article Number     | 151XADEKWFKW180   |
| EAN Code           | 7393969044639   |
| Surface Treatment  | Oil<br>This floor should be oiled immediately after installation. |
| Refining Treatment | Beveled 4-sided, Brushed, Smoked                                  |
| Dimensions         | 12 x 72 3/4 "   |
| Weight per Package | 44.1 lbs  |
| Area per Package   | 22 sqft   |
| Area per pallet    | 658.8 sqft  |
| Package info       | Packages may contain start and stop boards.                       |

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers.

### COLOR CHANGE

Smoked product - noticeable color change over time.

### FACTS

|                      |                    |
|----------------------|--------------------|
| Wood Species         | White Oak          |
| Design               | Pattern            |
| Grading              | Lively             |
| Range                | Kährs ID           |
| Collection           | Chevron Collection |
| Resandable           | 2 times            |
| Natural/Stained      | Stained            |
| Brinell Value        | 3,7                |
| Joint                | Tongue & Groove    |
| Floor heating        | Yes                |
| Warranty             | 30 years           |
| Warranty             | 20 years           |
| Wear-layer material  | Hardwood           |
| Wear Layer Thickness | 1/8"               |
| Core material        | Poplar             |
| Backside material    | Oak                |
| Thickness            | 5/8"               |
| Installation method  | Glue-Down          |
| Surface Color        | Dark brown         |

### TECHNICAL PROPERTIES

|  |                        |             |
|--|------------------------|-------------|
| Moisture content                       | EN13183                | 7%±2%       |
| Minimum Mean Density kg/m <sup>3</sup> | >500 kg/m <sup>3</sup> |             |
| Reaction To Fire                       | EN13501-1              | Dfl-s1      |
| Formaldehyde Emission                  | EN717-1                | E1          |
| Content PCP                            | CEN/TR14823            | ≤ 5 x 10-6n |
| Breaking Strength N/mm <sup>2</sup>    | EN1533                 | NPD         |
| Thermal Conductivity                   | EN12664                | 0,14 W/mK   |
| Thermal Resistance R-Value             | .11 (m2K/W)            |             |
| Biological Durability                  | EN350-2                | Class 1     |
| CARB2                                  | Compliant              |             |
| Slipperiness                           | CEN/TS15676            | NPD         |



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*