

OAK CHEVRON GREY

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three lamellas in a row between a left & right board. Chevron Grey is a warm brownish grey floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|--|---|----------------------|--------------------|--------------------------|--|-----------|
| Article Number | 151XADEKWKKW180 | Wood Species | Oak | Moisture | EN13183 | 7%±2% |
| EAN Code | 7393969044653 | Design | Pattern | content | | |
| Surface treatment | Oil This floor should be oiled immediately after installation. | Grading | Lively | Minimun Mean | Minimun Mean Density kg/m ³ | |
| | | Range | Kährs ID | Reaction To Fire | EN13501-1 EN717-1 | Dfl-s1 |
| | | Collection | Chevron Collection | Formaldehyde | | E1 |
| Design features | Bevelled 4-sided, Brushed | Resandable | 2-3 times | Emission | | |
| | | Natural/Stained | Stained | Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Dimensions | 305 x 1848 mm | Brinell Value | 3,7 | Breaking | EN1533 | NPD |
| Weight per Package | 20 kg | Joint | Tongue & Groove | Strength N/mm² | | |
| Area per Package | 2.04 m ² | Floor heating | Yes | Thermal | EN12664 | 0.14 W/mK |
| Area per pallet | 61.2 m ² | Warranty | 30 years | Conductivity | | |
| Package info | Packages may contain start and stop boards. | Warranty US | 20 years | Thermal Resista | Thermal Resistance R-Value | |
| | | Wear-layer material | Hardwood | Biological Durability | EN350-2 | Class 1 |
| DETAIL DESCRIPTION | | Wear Layer Thickness | 3.5 mm | CARB2 | | Compliant |
| Naturally occuring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers. COLOUR CHANGE | | Core material | Poplar | | Slipperiness CEN/TS15676 | |
| | | Backside material | Oak | Suppermess | | INI D |
| | | Thickness | 15 mm | | | |
| | | Installation method | Glue-down | | | |
| Stained product - noticable color change over time. Surface Colou | | Surface Colour | Grey | | | |

Other products in this collection







Oak Chevron Dark brown

Oak Chevron Light brown

Oak Chevron Grey

CERTIFICATES











Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.