CHEVRON GREY

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three strips in a row between a left & right board. Chevron Grey is a warm brownish grey floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	151XADEKWKKW180 / 7393969044653
Design / Wood Species	Chevron / White Oak
Surface Treatment / Natural/Stained	Oil / Stained
Refining Treatment	Beveled 4-sided, Brushed
Width x Length x Thickness	12 x 72 3/4 x 5/8"
Weight per package / per m2	44.1 lbs / 21.6 lbs
Area per package / per pallet	22 sqft / 658.8 sqft
Grading	Lively
Joint	Tongue & Groove
Installation method	Glue-Down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 1/8"
Resandable	2 times
Core material	Poplar
Backside material	Oak

PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
LRV / LRV Std1	14 / 2.6
Warranty	20 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m³		>500 kg/m³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

TSCA TITLE VI & CARB P2 Compliant M1› CE

DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.
The product includes medium sound and black knots. Knots may vary in size and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.