

## CHEVRON GREY

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three strips in a row between a left & right board. Chevron Grey is a warm brownish grey floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil.

PRODUCT DETAILS		PRODUCT DETAIL
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brinell) va
Article Number / EAN Code	151XADEKWKKW180 / 7393969044653	range
Design / Wood Species	Chevron / White Oak	LRV / LRV Std1
Surface Treatment /	Oil / Stained	Warranty
Natural/Stained		— TECHNICAL PROP
Refining Treatment	Beveled 4-sided, Brushed	— Moisture content
Width x Length x Thickness	12 x 72 3/4 x 5/8"	— Minimun Mean Den
Weight per package / per	44.1 lbs / 21.6 lbs	kg/m <sup>3</sup>
m2		— Reaction To Fire
Area per package / per	22 sqft / 658.8 sqft	Formaldehyde Emis
pallet		Content PCP
Grading	Lively	— Breaking Strength N
Joint	Tongue & Groove	Biological Durability
Installation method	Glue-Down	— CARB2
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 1/8"	Slip resistance
thickness		TSCA UNISSION CLASS
Resandable	2 times	CARB P2
Core material	Poplar	Compliant ON ON
Backside material	Oak	

PRODUCT DETAI	LS
---------------	----

Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	
LRV / LRV Std1	14 / 2.6
Warranty	20 years

## PERTIES

TECHNICAL FROTERILLS		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m <sup>3</sup>
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



## **DETAILED DESCRIPTION**

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes medium sound and black knots. Knots may vary in size and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

