



OAK OMBRA

Hints of cinnamon are shot through with a deep-grey grain on this single-strip oak floor from the Boardwalk Collection. Each board has been hand brushed to bring out the grain and enhance the generous scattering of knots. Four-sided beveling creates a classic full plank look.

PRODUCT DETAILS

| | |
|--------------------|---|
| Article Number | 151NDMEK13KW240 |
| EAN Code | 7393969046107 |
| Surface treatment | Oil This floor should be oiled immediately after installation. |
| Design features | Microbevelled 4-sided, Brushed, Light smoked |
| Dimensions | 187 x 2420 mm |
| Weight per Package | 22 kg |
| Area per Package | 2.72 m ² |
| Area per pallet | 122.4 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots. Knots, fillings and cracks will be present in all sizes and numbers. The smoked design enhances the natural colour variations and creates a stronger contrast between light and dark.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|----------------------|----------------------|
| Wood Species | Oak |
| Design | 1-strip |
| Grading | Dynamic |
| Range | Kährs Original |
| Collection | Boardwalk Collection |
| Resandable | 2-3 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Warranty US | 25 years |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 3.5 mm |
| Core material | Pine/Spruce/Alder |
| Backside material | Spruce |
| Thickness | 15 mm |
| Installation method | Floating, Glue-down |
| Surface Colour | Grey |

TECHNICAL PROPERTIES

| | | |
|--|------------------------|-----------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m ³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slipperiness | CEN/TS15676 | NPD |

Other products in this collection



Oak Luce



Oak Ombra



Oak Pallido



Oak Tramonto

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.