



OAK CHEVRON LIGHT BROWN

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three lamellas in a row between a left & right board. Chevron Light Brown is a warm oak floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

PRODUCT DETAILS

Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	151XADEKWJKW180 / 7393969044646
Design / Wood Species	Chevron / Oak
Surface treatment / Natural/Stained	Oil / Stained
Design features	Bevelled 4-sided, Brushed, Light smoked
Width x Length x Thickness	305 x 1848 x 15 mm
Weight per package / per m2	20 kg / 9.8 kg
Area per package / per pallet	2.04 m ² / 61.2 m ²
Grading	Lively
Joint	Tongue & Groove
Installation method	Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 3.5 mm
Resandable	2-3 times
Core material	Poplar
Backside material	Oak

PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
Warranty	30 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.
The product includes medium sound and black knots. Knots may vary in size and numbers..

- Oil:** This floor should be oiled immediately after installation.
- Colour change:** Stained product - noticable color change over time.
- Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection



OAK CHEVRON DARK BROWN