



## OAK CHEVRON LIGHT BROWN

The lightly smoked finish this on this ready-to-install, patterned oak board from the Chevron Collection enriches its warm toffee hue and brings a modern expression to its traditional look. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Partial handcrafting gives each board its unique appearance, while micro-bevelling enhances the iconic geometric design. A package contains an even split of left and right hand sided Chevron patterned boards. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

### PRODUCT DETAILS

<b>Article Number</b>	151XADEKWJKW180
<b>EANCode</b>	7393969044646
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Design features</b>	Bevelled 4-sided, Brushed, Light smoked
<b>Dimensions</b>	1848 x 305 x 15 mm
<b>Weight per Package x</b>	20.01 kg
<b>Area per Package x</b>	2.04 m <sup>2</sup>
<b>AreaPerPalletM2</b>	61.2
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium sound and black knots. Knots may vary in size and numbers..

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	Pattern
<b>Grading</b>	Lively
<b>Range</b>	Kährs ID
<b>Collection</b>	Chevron Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Tongue & Groove
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	3.5 mm
<b>Core material</b>	Poplar
<b>Thickness</b>	15 mm
<b>Surface Colour</b>	Mature oak

### TECHNICAL PROPERTIES

<b>TestMoistureContent</b>	7%±2%
<b>TestMinimunMeanDensity</b>	>500 kg/m <sup>3</sup>
<b>TestReactionToFire</b>	Dfl-s1
<b>TestFormaldehydeEmission</b>	E1
<b>TestContentPCP</b>	≤ 5 x 10-6n
<b>TestBreakingStrength</b>	NPD
<b>TestThermalConductivity</b>	0,14 W/mK
<b>TestThermalResistanceRValue</b>	.11 (m <sup>2</sup> K/W)
<b>TestBiologDurability</b>	Class 1
<b>TestCarb2</b>	Compliant



**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*