



OAK CHEVRON LIGHT BROWN

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three lamellas in a row between a left & right board. Chevron Light Brown is a warm oak floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil Matt.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	151XADEKWJKW180 / 7393969044646
Design / Wood Species	Chevron / Oak
Surface Treatment /	Oil / Stained
Natural/Stained	
Refining Treatment	Bevelled 4-sided, Brushed, Light smoked
Width x Length x Thickness	305 x 1848 x 15 mm
Weight per package / per	20 kg / 9.8 kg
m2	
Area per package / per	2.04 m ² / 61.2 m ²
pallet	
Grading	Lively
Joint	Tongue & Groove
Installation method	Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm
thickness	
Resandable	2-3 times
Core material	Poplar
Backside material	Oak

PRC	DU	CT	DE.	ΓΑΙ	LS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

DDODLICT DETAIL C

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes medium sound and black knots. Knots may vary in size and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

