



## CHEVRON LIGHT BROWN

Chevron boards are partially hand-made, giving a unique appearance to every board. Therefore, the tolerance of bevel precision has an allowance of 3 mm for a maximum of three strips in a row between a left & right board. Chevron Light Brown is a warm oak floor with occasional knots, cracks and fillings. This product requires an, after installation, maintenance treatment using Kährs Satin Oil.

Wood Flooring / 3-layer engineered
151XADEKWJKW180 / 7393969044646
Chevron / White Oak
Oil / Stained
Beveled 4-sided, Brushed, Light smoked
12 x 72 3/4 x 5/8"
44.1 lbs / 21.6 lbs
22 sqft / 658.8 sqft
Lively
Tongue & Groove
Glue-Down
Yes
Hardwood / 1/8"
2 times
Poplar
Oak

## PRODUCT DETAILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	20 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







## DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes medium sound and black knots. Knots may vary in size and numbers.

 $\begin{tabular}{ll} \textbf{Oil:} This floor should be oiled immediately after installation. \\ \end{tabular}$ 

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

