



OAK ASTER OILED 242

In Oak Aster the natural oak is left to shine in all its own glory with no staining, allowing the warm colour of the oak to penetrate the oiled surface uninhibited. Each board is carefully brushed, accentuating the natural wood grain while softening the texture, knots and cracks. Any contrast in colour are purely natural, letting the raw material speak for itself. Oak Aster is also available in a matt lacquered version.

	PRODUCT DETAILS		
Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
131246240 / 7393969306843	range		
Plank / Oak	LRV / LRV Std1 / LRV Std2	40 / 4.4 / 8.8	
Oil / Natural	Warranty	20 years	
	TECHNICAL DEODEDTIES		
Microbevelled 4-sided, Brushed			7%±2%
187 x 2420 x 13 mm		LIVIDIOD	>500 kg/m ³
22.5 kg / 7.02 kg	,		>300 Kg/III
		EN13501_1	Dfl-s1
3.17 m ² / 142.65 m ²			E1
			≤ 5 ppm
Dynamic			NPD
Woodloc® 5G			0,11W/mK
Floating, Glue-down			Class 1
Yes		LINSSU-Z	Compliant
Hardwood / 2.6 mm		CEN/TC1E676	NPD
	slip resistance	CEN/13130/0	NFD
2-3 times	SMERICHE DANS LINE STEEREN		
Pine/Spruce			
Spruce			
	131246240 / 7393969306843 Plank / Oak Oil / Natural Microbevelled 4-sided, Brushed 187 x 2420 x 13 mm 22.5 kg / 7.02 kg 3.17 m² / 142.65 m² Dynamic Woodloc® 5G Floating, Glue-down Yes Hardwood / 2.6 mm 2-3 times Pine/Spruce	Wood Floors / 3-layer parquet 131246240 / 7393969306843 Plank / Oak Oil / Natural Microbevelled 4-sided, Brushed 187 x 2420 x 13 mm 22.5 kg / 7.02 kg 3.17 m² / 142.65 m² Ploating, Glue-down Yes Hardwood / 2.6 mm Hardness (Brinell) value / range LRV / LRV Std1 / LRV Std2 Warranty TECHNICAL PROPERTIES Moisture content Minimun Mean Density kg/m³ Reaction To Fire Formaldehyde Emission Content PCP Breaking Strength N/mm² Thermal Conductivity Biological Durability CARB2 Slip resistance	Wood Floors / 3-layer parquet 131246240 / 7393969306843 Plank / Oak Oil / Natural Microbevelled 4-sided, Brushed 187 x 2420 x 13 mm 22.5 kg / 7.02 kg Dynamic Woodloc® 5G Floating, Glue-down Yes Hardwood / 2.6 mm Plank / Oak LRV / LRV Std1 / LRV Std2 40 / 4.4 / 8.8 Warranty 20 years TECHNICAL PROPERTIES Moisture content EN13183 Minimun Mean Density kg/m³ Reaction To Fire EN13501-1 Formaldehyde Emission EN717-1 Content PCP CEN/TR14823 Breaking Strength N/mm² EN1533 Thermal Conductivity EN12664 Biological Durability EN350-2 CARB2 Slip resistance CEN/TS15676

DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

 $\begin{tabular}{ll} \textbf{Oil:} This floor should be oiled immediately after installation. \\ \end{tabular}$

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection

OAK LUPINE

OAK LAVENDER



OAK ZINNIA