

OAK PALLIDO

The barely-there sepia stain on this single-strip oak floor from the Boardwalk Collection allows natural tones to show through, while highlighting a characterful formation of knots and cracks. Each board is carefully brushed to bring out the grain and four-sided beveling ensures a classic full plank look.

| PRODUCT DETAILS | | PRODUCT DETAILS | | |
|-----------------------------|--|-------------------------------------|-----------------|------------------------|
| Product type / Construction | Wood Floors / 3-layer parquet | Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| Article Number / EAN Code | 151NDMEK10KW240 / 7393969046084 | range | | |
| Design / Wood Species | 1-strip / Oak | LRV / LRV Std1 | 29 / 7.4 | |
| Surface treatment / | Oil / Stained | Warranty | 30 years | |
| Natural/Stained | | TECHNICAL PROPERTIES | | |
| Design features | Microbevelled 4-sided, Brushed | — Moisture content | EN13183 | 7%±2% |
| Width x Length x Thickness | 187 x 2420 x 15 mm | | ENTST83 | >500 kg/m ³ |
| Weight per package / per | 22 kg / 8.15 kg | — Minimun Mean Density kg/m³ | | >500 kg/111- |
| m2 | | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Area per package / per | 2.72 m ² / 122.4 m ² | Formaldehyde Emission | EN717-1 | E1 |
| pallet | | — Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Grading | Dynamic | Breaking Strength N/mm ² | EN1533 | NPD |
| Joint | Woodloc® 5S | — Thermal Conductivity | EN12664 | 0,11W/mK |
| Installation method | Floating, Glue-down | — Biological Durability | EN350-2 | Class 1 |
| Floor heating | Yes | — CARB2 | 2113302 | Compliant |
| Wear leayer material / | Hardwood / 3.5 mm | Slip resistance | CEN/TS15676 | NPD |
| thickness | | Slip resistance | CEIV/1313070 | INFU |
| Resandable | 2-3 times | | 6 T | FILOOR FILOR |
| Core material | Pine/Spruce/Alder | | BASTA | A+ score |
| Backside material | Spruce | Compliant SundaHus | DAJIA | C Sta Gabail Services |

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots. Knots, fillings and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | [©]Kährs 2025-08-15

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK LUCE



OAK OMBRA



OAK PALLIDO



OAK TRAMONTO