



OAK PALLIDO

The barely-there sepia stain on this single-strip oak floor from the Boardwalk Collection allows natural tones to show through, while highlighting a characterful formation of knots and cracks. Each board is carefully brushed to bring out the grain and four-sided beveling ensures a classic full plank look.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2
Article Number / EAN Code	151NDMEK10KW240 / 7393969046084	range	
Design / Wood Species	1-strip / Oak	LRV / LRV Std1	29 / 7
Surface Treatment /	Oil / Stained	Warranty	30 yea
Natural/Stained		— TECHNICAL PROPERTIES	
Refining Treatment	Microbevelled 4-sided, Brushed	— Moisture content EN13	
Width x Length x Thickness	187 x 2420 x 15 mm	— Minimun Mean Density kg/m³	
Weight per package / per	22 kg / 8.15 kg		
m2		— Reaction To Fire	EN135
Area per package / per	2.72 m ² / 122.4 m ²	Formaldehyde Emission EN7	
pallet		— Content PCP	CEN/T
Grading	Dynamic	Breaking Strength N/mm ² EN153	
Joint	Woodloc® 5S		
Installation method	Floating, Glue-down		
Floor heating	Yes	CARB2Slip resistanceCEN/T:	
Wear leayer material /	Hardwood / 3.5 mm	Slip resistance	CEIV/ I
thickness		M1) M1 M2 M1 M2 M2 M3 M3 M3 M3 M3 M3 M3 M3	
Resandable	2-3 times		
Core material	Pine/Spruce/Alder		

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
LRV / LRV Std1	29 / 7.4	
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³

Willillian Mean Density		2300 Kg/III
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Backside material

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots. Knots, fillings and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Spruce

Packages may contain start and stop boards.

Other products in this collection









OAK LUCE OAK OMBRA

OAK PALLIDO OAK TRAMONTO