



OAK OVIS

Oak Ovis brings together the gentle warmth of natural oak with the softly diffused character of Rohoptic Oil. The surface carries a subtle, powdery patina that feels both modern and timeless. Deep brushing follows every rise and fall of the grain, adding quiet movement, while naturally occurring knots are hand-repaired to preserve authenticity without overpowering the design. A 4-sided micro-bevel lends a light, tailored shadow, defining each board with precision.

PRODUCT DETAILS

Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	131272220 / 7393969306874
Design / Wood Species	Plank / Oak
Surface treatment / Natural/Stained	Oil / Stained
Design features	Microbevelled 4-sided, Brushed
Width x Length x Thickness	187 x 2266 x 13 mm
Weight per package / per m ²	24 kg / 7.19 kg
Area per package / per pallet	3.39 m ² / 118.65 m ²
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear layer material / thickness	Hardwood / 2.6 mm
Resandable	2-3 times
Core material	Pine/Spruce
Backside material	Spruce

PRODUCT DETAILS

Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
LRV / LRV Std1 / LRV Std2	39 / 4.2 / 8.4
Warranty	20 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

All naturally occurring wood color variations are allowed, ranging from light to dark brown tones. Sapwood may be present. The product features very large sound and black knots, as well as natural cracks. Knot holes and cracks are repaired with a dark filler, and larger openings may be plugged with knot inserts.

Oil: This floor should be oiled immediately after installation.


Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.


Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.


Other products in this collection



OAK URSUS



OAK LARUS



OAK OVIS



OAK LYNX OILED



OAK LYNX ULTRA MATT