



DAINTREE CLW 218

DESCRIPTION DU PRODUIT

Type de produit / Construction	Sol vinyle / Click SPC LVT
Code article / Code EAN	LTCLW2106-218 / 7393969110174
Style	Tile Design
Largeur x Longueur x Épaisseur	218 x 1210 x 6 mm
Poids par paquet / par m2	20,6 kg / 9,81 kg
Surface par paquet / par palette	2,1 m² / 84,5 m²

INFORMATIONS

Joint d'assemblage	Click5G
Pose	Flottante
Chauffage au sol	Oui
Couche d'usure épaisseur	0,55 mm
Garantie	30 ans

CARACTÉRISTIQUES TECHNIQUES

Application	EN ISO 10874	23/33/42
Emission of formaldehyde	E1	
Réaction au feu	EN13501-1	Bfl-s1

CARACTÉRISTIQUES TECHNIQUES

Emission de Formaldéhyde	EN717-1	E1
Valeur Résistance thermique		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and fungi		Good
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Commercial usage classification	EN 14354:2017	Class 33



