



Canvas Collection



## OAK MOREL

Oak Sacra have a 1-strip design, matt finish and some knots.

### PRODUCT DETAILS

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Product type / Construction         | Wood Flooring / 3-layer engineered |
| Article Number / EAN Code           | 13103AEK1IKW185 / 7393969043083    |
| Design / Wood Species               | 1-strip / White Oak                |
| Surface Treatment / Natural/Stained | Matte finish / Stained             |
| Refining Treatment                  | Microbeveled 4-sided, Brushed      |
| Width x Length x Thickness          | 5 x 73 1/4 x 1/2"                  |
| Weight per package / per m2         | 28 lbs / 16.9 lbs                  |
| Area per package / per pallet       | 17.8 sqft / 1120.3 sqft            |
| Grading                             | Variation                          |
| Joint                               | Woodloc®                           |
| Installation method                 | Floating, Glue-Down                |
| Floor heating                       | Yes                                |
| Wear leayer material / thickness    | Hardwood / 1/8"                    |
| Resandable                          | 2 times                            |
| Core material                       | Pine/Spruce                        |
| Hardness (Brinell) value / range    | 3,7 / 2.2 - 5.9                    |

### PRODUCT DETAILS

|                               |             |             |
|-------------------------------|-------------|-------------|
| Warranty                      | 25 years    |             |
| TECHNICAL PROPERTIES          |             |             |
| Moisture content              | EN13183     | 7%±2%       |
| Minimun Mean Density<br>kg/m³ | >500 kg/m³  |             |
| Reaction To Fire              | EN13501-1   | Dfl-s1      |
| Formaldehyde Emission         | EN717-1     | E1          |
| Content PCP                   | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm²       | EN1533      | NPD         |
| Thermal Conductivity          | EN12664     | 0,08 W/mK   |
| Thermal Resistance R-Value    | .15 (m2K/W) |             |
| Biological Durability         | EN350-2     | Class 1     |
| CARB2                         | Compliant   |             |
| Slip resistance               | CEN/TS15676 | NPD         |



### DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

**Colour change:** Stained product - noticable color change over time.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |  
www.kahrs.com | ©Kährs,  
USA & Canada 2025-08-31

Other products in this collection



Oak Weathered



Oak Russet



Oak Latte



OAK ECRU



Oak Fawn



Oak Henna



Oak Cadence




Oak Pratica



Oak Reiter



Oak Morel



Oak Muse



Oak Tapa



Oak Curio




Oak Carbon



Oak Etch



Oak Tuft



Oak Mostra