



## OAK REITER

The soft blonde tones in this single-strip oak floor from the Canvas Collection are enhanced by a chalky-grey stain resulting in a clean expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic full plank look and feel.

| PRODUCT DETAILS   |   | FACTS                |                     | TECHNICAL PROPERTIES                  |             |             |
|---|---|----------------------|---------------------|---------------------------------------|-------------|-------------|
| Article Number  | 13103AEK1UKW185                             | Wood Species         | Oak                 | Moisture                              | EN13183     | 7%±2%       |
| EAN Code  | 7393969043113                               | Design               | 1-strip             | content                               |             |             |
| Surface treatment   | Matt lacquer                                | Grading              | Variation           | Minimun Mean Density kg/m³ >500 kg/m³ |             |             |
| Design features   | Microbevelled 4-sided,<br>Brushed           | Range                | Kährs Avanti        | Reaction To<br>Fire                   | EN13501-1   | Dfl-s1      |
|   |   | Collection           | Canvas Collection   | Formaldehyde<br>Emission              | EN717-1     | E1          |
| Dimensions  | 127 x 1860 mm                               | Resandable           | 2-3 times           |                                       |             |             |
| Weight per Package  | 12.687 kg                                   | Natural/Stained      | Stained             | Content PCP                           | CEN/TR14823 | ≤ 5 ppm     |
| Area per Package  | 1.652 m <sup>2</sup>                        | Brinell Value        | 3,7                 | Breaking                              | EN1533      | NPD         |
| Area per pallet   | 104.076 m²                                  | loint                | Woodloc®            | Strength N/mm²                        |             |             |
| Package info  | Packages may contain start and stop boards. | Floor heating        | Yes                 | Thermal<br>Conductivity               | EN12664     | 0,08 W/mK   |
|   |   | Warranty             | 25 years            |                                       |             |             |
| DETAIL DESCRIPTION  |   | Warranty US          | 25 years            | Thermal Resistance R-Value            |             | .15 (m2K/W) |
| Even color with minor variations. Small to medium sized knots in limited numbers allowed. |   | Wear-layer material  | Hardwood            | Biological<br>Durability              | EN350-2     | Class 1     |
|   |   | Wear Layer Thickness | 3 mm                | CARB2                                 |             | Compliant   |
| COLOUR CHANGE Core material   |   | Core material        | Pine/Spruce lamella | Slipperiness                          | CEN/TS15676 | '           |
| Stained product - noticable color change over time.                                       |   | Thickness            | 13 mm               | 3nppermess                            | CEN/13130/0 | INFU        |
|   |   | Installation method  | Floating, Glue-down |                                       |             |             |

## Other products in this collection



## **CERTIFICATES**









## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.