

OAK REITER

Oak Chalk have a 1-strip design, matt finish and some knots.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	13103AEK1UKW185	Wood Species	White Oak	Moisture	EN13183	7%±2%
EAN Code	7393969043113	Design	1-strip	content		
Surface Treatment	Matte finish	Grading	Variation	Minimun Mean Density kg/m ³ >500 kg/m ³		
Refining Treatment	Microbeveled 4-sided, Brushed	Range	Kährs Avanti	Reaction To Fire	EN13501-1	Dfl-s1
		Collection	Canvas Collection	Formaldehyde Emission	EN717-1	E1
Dimensions	5 x 73 1/4 "	Resandable	2 times			
Weight per Package	28 lbs	Natural/Stained	Stained	Content PCP	CEN/TR14823	3 ≤ 5 x 10-6n
Area per Package	17.8 sqft	Brinell Value	3,7	Breaking	EN1533	NPD
Area per pallet	1120.3 sqft	Joint	Woodloc®	Strength N/mm ²		
Package info	Packages may contain start and stop boards.	Floor heating	Yes	Thermal	EN12664	0,08 W/mK
		Warranty	25 years	Conductivity		
DETAIL DESCRIPTION		Warranty	25 years	Thermal Resistance R-Value		.15 (m2K/W)
Even colour with minor variations. Small sized knots in limited numbers allowed.		Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1
		Wear Layer Thickness	1/8"	CARB2		Compliant
COLOR CHANGE		Core material	Pine/Spruce lamella	Slipperiness	CEN/TS15676	
Stained product - noticable color change over time.		Thickness	1/2"	Subbermess	CEN/1515070	
		Installation mothod	Electing Club Down			

Installation method

Floating, Glue-Down

Other products in this collection



Oak Tuft

Oak Mostra

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.