



## **OAK TRAMONTO**

PRODUCT DETAILS

This single-strip oak floor from the Boardwalk Collection creates a rustic expression with its warm honey hue and chestnut-brown grain. Characterful knots create a sense of texture that is brought to life with hand brushing. Four-sided beveling creates a classic full plank look,

|  | PRODUCT DE   |
|--|--|
| Wood Floors / 3-layer parquet              | Hardness (Brine  |
| 151NDMEK14KW240 / 7393969046114            | range  |
| 1-strip / Oak                              | LRV / LRV Std1   |
| Oil / Natural                              | Warranty   |
|  | — TECHNICAL P  |
| Microbevelled 4-sided, Brushed, Smoked     | — Moisture conte   |
| 187 x 2420 x 15 mm                         | — Minimun Mean   |
| 22 kg / 8.15 kg                            | kg/m³  |
|  | — Reaction To Fire   |
| 2.72 m <sup>2</sup> / 122.4 m <sup>2</sup> | Formaldehyde   |
|  | — Content PCP  |
| Dynamic                                    | Breaking Streng  |
| Woodloc® 5S                                | Thermal Condu  |
| Floating, Glue-down                        |  |
| Yes  | <ul><li>Biological Dural</li><li>CARB2</li></ul>   |
| Hardwood / 3.5 mm                          |  |
|  | Slip resistance  |
| 2-3 times                                  | TSCA   |
| Pine/Spruce/Alder                          | CARB P2  |
| Spruce                                     | Compliant Sund   |
|  | 151NDMEK14KW240 / 7393969046114  1-strip / Oak Oil / Natural  Microbevelled 4-sided, Brushed, Smoked 187 x 2420 x 15 mm 22 kg / 8.15 kg  2.72 m² / 122.4 m²  Dynamic  Woodloc® 5S Floating, Glue-down Yes Hardwood / 3.5 mm  2-3 times Pine/Spruce/Alder |

| PROD | DUCT | <b>DETAI</b> | LS |
|------|------|--------------|----|
|------|------|--------------|----|

| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 |            |
|----------------------------|-----------------|------------|
| range                      |                 |            |
| LRV / LRV Std1             | 18 / 4.5        |            |
| Warranty                   | 30 years        |            |
| - TECHNICAL PROPERTIES     | 5               |            |
| - Moisture content         | EN13183         | 7%±2%      |
| Minimun Mean Density       |                 | >500 kg/m³ |
| kg/m³                      |                 |            |
| Reaction To Fire           | EN13501-1       | Dfl-s1     |
| Formaldehyde Emission      | EN717-1         | E1         |
| - Content PCP              | CEN/TR14823     | ≤ 5 ppm    |
| Breaking Strength N/mm²    | EN1533          | NPD        |
| Thermal Conductivity       | EN12664         | 0,11W/mK   |
| Biological Durability      | EN350-2         | Class 1    |
| - CARB2                    | _               | Compliant  |









CEN/TS15676





NPD





## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots. Knots, fillings and cracks will be present in all sizes and numbers. The smoked design enhances the natural colour variations and creates a stronger contrast between light and dark.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticeable color change over time

Packages may contain start and stop boards.

**Descriptions & Imagery** 

www.kahrs.com | ©Kährs

## Other products in this collection









OAK LUCE OAK OMBRA

OAK PALLIDO OA