



## OAK CARBON

The smoky brown nuances of this single-strip oak floor from the Canvas Collection range from light to dark, and are stippled with a striking variety of knots for a rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer engineered	LRV / LRV Std1	
Article Number / EAN Code	13106AEK1RKW185 / 7393969044035	Warranty	
Design / Wood Species	1-strip / White Oak	— TECHNICAL PROPERTIES	
Surface Treatment /	Matte finish / Stained		
Natural/Stained		Moisture content	
Refining Treatment	Microbeveled 4-sided, Brushed	<ul> <li>Minimun Mean Density</li> <li>kg/m³</li> </ul>	
Width x Length x Thickness	5 x 73 1/4 x 1/2"		
Weight per package / per	28 lbs / 16.9 lbs	Reaction To Fire	
m2		Formaldehyde Emission	
_	17.9 caft / 1120.2 caft	Content PCP	
Area per package / per	17.8 sqft / 1120.3 sqft	Breaking Strength N/mm <sup>2</sup>	
pallet		Thermal Conductivity	
Grading	Lively	Thermal Resistance R-Value	
Joint	Woodloc® 5G	— Biological Durability	
Installation method	Floating, Glue-Down	— CARB2	
Floor heating	Yes	-	
Wear leayer material /	Hardwood / 1/8"	Slip resistance	
thickness		TSCA floor	
Resandable	2 times	CARB P2	
Core material	Pine/Spruce lamella	Compliant Compliant	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9		
range			

PRODU	CT	DETAIL	C
PRODU	J C I	DETAIL	_>

LRV / LRV Std1	16 / 1.9	
Warranty	25 years	
— TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
— kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,08 W/mK

EN350-2

CEN/TS15676







## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

.15 (m2K/W)

Class 1

NPD

Compliant

## Other products in this collection

Oak Tuft

Oak Mostra

