



# OAK CURIO

The charcoal-brown hues found in this single-strip oak floor from the Canvas Collection range from dark to light. Natural variations in the timber, alongside mottled knots and cracks, give it a rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
<b>Article Number</b>	13106AEKA1KW185	<b>Wood Species</b>	White Oak	<b>Moisture content</b>	EN13183	7%±2%
<b>EAN Code</b>	7393969043915	<b>Design</b>	1-strip	<b>Minimum Mean Density kg/m³</b>	>500 kg/m³	
<b>Surface Treatment</b>	Matte finish	<b>Grading</b>	Lively	<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Refining Treatment</b>	Microbeveled 4-sided, Brushed	<b>Range</b>	Kährs Avanti	<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Dimensions</b>	73 1/4 x 5 x 1/2"	<b>Collection</b>	Canvas Collection	<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Weight per Package</b>	28 lbs	<b>Resandable</b>	2 times	<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Area per Package</b>	17.8 sqft	<b>Natural/Stained</b>	Stained	<b>Thermal Conductivity</b>	EN12664	0,08 W/mK
<b>Area per pallet (m²)</b>	1120.3 sqft	<b>Brinell Value</b>	3,7	<b>Thermal Resistance R-Value</b>	.15 (m2K/W)	
<b>Package info</b>	Packages may contain start and stop boards.	<b>Joint</b>	Woodloc® 5G	<b>Biological Durability</b>	EN350-2	Class 1
<b>DETAIL DESCRIPTION</b>	All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		<b>Floor heating</b>	Yes	<b>CARB2</b>	Compliant
<b>COLOR CHANGE</b>	Stained product - noticeable color change over time.			25 years		
		<b>Wear-layer material</b>	Hardwood			
		<b>Wear-layer thickness</b>	1/8"			
		<b>Core material</b>	Pine/Spruce lamella			
		<b>Thickness</b>	1/2"			
		<b>Surface Color</b>	Dark brown			
		<b>Installation method</b>	Floating, Glue-Down			



### **Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*