



OAK KLINTA

The transparent white stain on this single-strip oak floor from the Småland Collection creates a natural pale impression. Each board is meticulously hand-scraped which highlights the knots and the balanced rustic appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS

| | |
|---------------------------|---|
| Article Number | 151NCSEK07KW240 |
| EAN Code | 7393969044820 |
| Surface Treatment | Oil This floor should be oiled immediately after installation. |
| Refining Treatment | Beveled 4-sided, Brushed, Handscraped |
| Dimensions | 7 3/8 x 95 1/4 " |
| Weight per Package | 48.5 lbs |
| Area per Package | 29.1 sqft |
| Area per pallet | 1317.5 sqft |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | White Oak |
| Design | 1-strip |
| Grading | Dynamic |
| Range | Kährs Supreme |
| Collection | Småland Collection |
| Resandable | 2 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Warranty | 20 years |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 1/8" |
| Core material | Pine/Spruce lamella |
| Backside material | Veneer |
| Thickness | 5/8" |
| Installation method | Floating, Glue-Down |
| Surface Color | White |

TECHNICAL PROPERTIES

| | | |
|-----------------------------------|-------------|-------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m2K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slipperiness | CEN/TS15676 | NPD |

Other products in this collection



Oak Klinta



Sevede



Ydre



Möre



Vista



Vedbo



Handbörd



Tveta



Finnveden



Aspeland

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.