



OAK PARIS ULTRA MATT 226

The blonde nuances in this white, single-strip floor from the Capital Collection are balanced by an even colour variation between planks. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel.

| PRODUCT DETAILS | | | |
|-----------------------------|---|--|--|
| Product type / Construction | Wood Floors / 3-layer parquet | | |
| Article Number / EAN Code | 151N4AEK4JKW220 / 7393969044967 | | |
| Design / Wood Species | 1-strip / Oak | | |
| Surface treatment / | Ultra matt lacquer / Stained | | |
| Natural/Stained | | | |
| Design features | Microbevelled 4-sided, Brushed | | |
| Width x Length x Thickness | 187 x 2266 x 15 mm | | |
| Weight per package / per | 21 kg / 8.4 kg | | |
| m2 | | | |
| Area per package / per | 2.5 m ² / 114.3 m ² | | |
| pallet | | | |
| Grading | Calm | | |
| Joint | Woodloc® 5S | | |
| Installation method | Floating, Glue-down | | |
| Floor heating | Yes | | |
| Wear leayer material / | Hardwood / 3.5 mm | | |
| thickness | | | |
| Resandable | 2-3 times | | |
| Core material | Pine/Spruce lamella | | |
| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | | |
| range | | | |

| _ | RU | טט | CI | DE | IAIL | _S |
|---|----|----|----|----|------|----|
| | | | | | | |

| LRV / LRV Std1 | 38 / 3.5 | |
|----------------------------|-------------|-------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | 5 | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Thermal Resistance R-Value | 2 | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |



Slip resistance







CEN/TS15676





NPD







DETAILED DESCRIPTION

PRODUCT DETAILS

Even colour with minor variations.

Small sized knots in limited numbers allowed.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection



OAK PARIS ULTRA MATT



OAK DUBLIN ULTRA MATT NARROW



OAK PARIS ULTRA MATT NARROW / HONEY OAT



OAK PRAGUE



OAK BERLIN



OAK PARIS OILED



OAK DUBLIN OILED