



OAK DUBLIN

The light honey nuances in this single-strip oak floor from the Capital Collection range from faint tan to pale golden brown, giving it an even colouring. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DETAILS

| | |
|---|---|
| Article Number | 151N4AEK04KW240 |
| EAN Code | 7393969044950 |
| Surface treatment | Ultra matt lacquer The appearance of the matte surface may vary due to different light sources and angles. |
| Design features | Microbevelled 4-sided, Brushed |
| Dimensions | 2420 x 187 x 15 mm |
| Weight per Package (kg) | 22 kg |
| Area per Package (m²) | 2.7 m ² |
| Area per pallet (m²) | 114.3 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Board | 1-strip |
| Grading | Calm |
| Range | Kährs Original |
| Collection | Capital Collection |
| Resandable | 2-3 times |
| Natural/Stained | Natural |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3.5 mm |
| Core material | Pine/Spruce lamella |
| Thickness | 15 mm |
| Installation method | Floating, Glue-down |

TECHNICAL PROPERTIES

| | | |
|--|--------------------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m ² K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.