



SAND OAK

The calming coral hue of this single-strip oak floor in the Unity Collection is lifted by pale white highlights, sand-colour lowlights and a few scattered knots. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DETAILS FACTS			TECHNICAL PROPERTIES		
101P3AEKBCKW180	Wood Species	Oak	Moisture	EN13183	7%±2%
7393969030694	Design	1-strip			
Matt lacquer	Grading	Variation	Minimun Mean Density kg/m³ >800 kg/m³		
Bevelled 4-sided,	Range	Kährs Spirit	Reaction To Fire	EN13501-1	Cfl-s1
Brushed	Collection	Unity Collection	Formaldehyde	EN717-1	E1
125 x 1830 mm	Resandable	1 time	Emission		
16.8 kg	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 ppm
1.8 m ²	loint	Woodloc®	Breaking	EN1533	NPD
89.7 m ²	Floor heating	Yes	Strength N/mm²		
Package info Packages may contain start and stop boards.	Wear-layer material	Hardwood	Thermal EN1266 Conductivity	EN12664	1 0,14 W/mK
	Wear Layer Thickness	1.9 mm			
	Core material	HDF	Thermal Resista	ance R-Value	.07 (m2K/W)
Even colour with minor variations. Small sized knots in limited numbers allowed. Backside material and the state of the s		Veneer	Biological Durability	EN350-2	Class 1
		10 mm	CARB2		Compliant
	Installation method	Glue-down, Floating		CEN/TS15676	· ·
Stained product - noticable color change over time. Surface Colour		White BC	Suppermess	CLIV/13130/0	INI D
	7393969030694 Matt lacquer Bevelled 4-sided, Brushed 125 x 1830 mm 16.8 kg 1.8 m² 89.7 m² Packages may contain start and stop boards.	101P3AEKBCKW180 Posign Matt lacquer Bevelled 4-sided, Brushed Collection Resandable 16.8 kg Natural/Stained Joint Floor heating Wear-layer material Wear Layer Thickness Ved. Initalian method Backside material Thickness Installation method	101P3AEKBCKW180 Posign Design 1-strip Matt lacquer Bevelled 4-sided, Brushed 125 x 1830 mm 16.8 kg 1.8 m² Packages may contain start and stop boards. Packages. Wear-layer material Variation Wood Species Oak Package	101P3AEKBCKW180 Wood Species Oak Moisture content 7393969030694 Design 1-strip Matt lacquer Grading Variation Bevelled 4-sided, Brushed 125 x 1830 mm 16.8 kg Natural/Stained Stained 1.8 m² Packages may contain start and stop boards. Variations. Small sized knots ved. Variation Moisture content Minimun Mean Reaction To Fire Formaldehyde Emission Content PCP Stained Variations. Small sized knots ved. Moisture content Minimun Mean Reaction To Fire Formaldehyde Emission Content PCP Stained Variations Variations Natural/Stained Stained Content PCP Floor heating Yes N/mm² Wear-layer material Hardwood Thermal Conductivity Thermal Resistance Variations. Small sized knots ved. Moisture content Meariation Reaction To Fire Formaldehyde Emission Content PCP Thermal Resistance N/mm² Thermal Resistance Veneer Thickness 10 mm CARB2 Slipperiness	Total Pack Mood Species Oak Moisture content

Other products in this collection









Park Oak

Orchard Walnut

Garden Walnut

Arctic Oak

CERTIFICATES











Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.