



## OAK PARK

The natural tones in this single-strip oak floor from the Unity Collection range from dark chocolate to bleached straw, and are scattered with knots for an earthy, rustic expression. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

### PRODUCT DETAILS

|   |  |
|---|--|
| Product type / Construction             | Wood Flooring / Veneer floors            |
| Article Number / EAN Code               | 101P6AEK09KW180 / 7393969043762          |
| Design / Wood Species                   | 1-strip / Oak                            |
| Surface Treatment / Natural/Stained     | Matt lacquer / Natural                   |
| Refining Treatment                      | Bevelled 4-sided, Brushed                |
| Width x Length x Thickness              | 125 x 1830 x 10 mm                       |
| Weight per package / per m <sup>2</sup> | 16.8 kg / 9.33 kg                        |
| Area per package / per pallet           | 1.8 m <sup>2</sup> / 89.7 m <sup>2</sup> |
| Grading                                 | Lively                                   |
| Joint                                   | Woodloc®                                 |
| Installation method                     | Floating, Glue-down                      |
| Floor heating                           | Yes                                      |
| Wear layer material / thickness         | Hardwood / 1.9 mm                        |
| Core material                           | HDF                                      |
| Backside material                       | Veneer                                   |
| Warranty                                | 20 years                                 |

### TECHNICAL PROPERTIES

|                                     |             |                          |
|-------------------------------------|-------------|--------------------------|
| Moisture content                    | EN13183     | 7%±2%                    |
| Minimum Mean Density                |             | >800 kg/m <sup>3</sup>   |
| Reaction To Fire                    | EN13501-1   | Cfl-s1                   |
| Formaldehyde Emission               | EN717-1     | E1                       |
| Content PCP                         | CEN/TR14823 | ≤ 5 x 10 <sup>-6</sup> n |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                      |
| Thermal Conductivity                | EN12664     | 0,14 W/mK                |
| Thermal Resistance R-Value          |             | .07 (m <sup>2</sup> K/W) |
| Biological Durability               | EN350-2     | Class 1                  |
| CARB2                               |             | Compliant                |
| Slip resistance                     | CEN/TS15676 | NPD                      |



### DETAILED DESCRIPTION

**Colour change:** Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |  
www.kahrs.com | ©Kährs,  
United Kingdom & Ireland  
2026-04-09

## Other products in this collection



ARCTIC OAK