



## ARCTIC OAK

The blanched-oak boards of this single-strip, stained floor from the Unity Collection range in colour from creamy white to heather grey, punctuated by rustic knots. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

### PRODUCT DETAILS

<b>Article Number</b>	101P6AEKODKW180
<b>EAN Code</b>	7393969030656
<b>Surface treatment</b>	Matt lacquer
<b>Design features</b>	Bevelled 4-sided, Brushed
<b>Dimensions</b>	1830 x 125 x 10 mm
<b>Weight per Package (kg)</b>	16.80 kg
<b>Area per Package (m<sup>2</sup>)</b>	1.80 m <sup>2</sup>
<b>Area per pallet (m<sup>2</sup>)</b>	89.70 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots and cracks. Knots and cracks may vary in size and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Variation
<b>Range</b>	Kährs Spirit
<b>Collection</b>	Unity Collection
<b>Resandable</b>	1 time
<b>Natural/Stained</b>	Stained
<b>Joint</b>	Woodloc®
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1.9 mm
<b>Core material</b>	HDF
<b>Thickness</b>	10 mm
<b>Surface Colour</b>	White 0W
<b>Installation method</b>	Floating, Glue-down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>800 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Cfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.07 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*