



OAK REEF

The natural shades of this oak single-strip floor in the Unity Collection, range from subtle tawny to sunset umbers and chocolate browns with just a few scattered knots. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / Veneer floors	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	101P3AEK09KW180 / 7393969043755	range		
Design / Wood Species	Plank / Oak	Warranty	20 years	
Surface treatment /	Matt lacquer / Natural	TECHNICAL PROPERTIES		
Natural/Stained		Moisture content	EN13183	7%±2%
Design features	Bevelled 4-sided, Brushed	— Minimun Mean Density	LINISTOS	
Width x Length x Thickness	125 x 1830 x 10 mm			>800 kg/m ³
Weight per package / per	16.8 kg / 9.33 kg	Reaction To Fire	EN13501-1	Cfl-s1
m2		Formaldehyde Emission	EN717-1	E1
Area per package / per	1.8 m ² / 89.7 m ²	Content PCP	CEN/TR14823	≤ 5 ppm
pallet		Breaking Strength N/mm ²	EN1533	NPD
Grading	Variation	— Thermal Conductivity	EN12664	0,14 W/mK
Joint	Woodloc®	Thermal Resistance R-Value		.07 (m2K/W)
Installation method	Floating, Glue-down	Biological Durability	EN350-2	Class 1
Floor heating	Yes	— CARB2	LINSSU-Z	Compliant
Wear leayer material /	Hardwood / 1.9 mm	Slip resistance	CEN/TS15676	NPD
thickness		Slip resistance	CLIV/1313070	NFD
Resandable	1 time	TSCA TITLE VI CARB P2 Compliant TSCA TITLE VI CARB P2 Total VI		
Core material	HDF			
Backside material	Veneer			

DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Other products in this collection



ARCTIC OAK