



OAK STUDIO AB SMOKED OILED

Smoked Oak AB is a clean dark brown oak with some colour variation and small knots with an oiled finish.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Flooring / 2-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	111PABEKFCKE050 / 7393969042376	Minimun Mean Density		>500 kg/m³
Design / Wood Species	Herringbone / Oak	kg/m³		
Surface Treatment /	Oil / Stained	Reaction To Fire	EN13501-1	Cfl-s1
Natural/Stained		Formaldehyde Emission	EN717-1	E1
Refining Treatment	Smoked	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Width x Length x Thickness	70 x 490 x 11 mm	Breaking Strength N/mm ²	EN1533	NPD
Weight per package / per	13.3 kg / 6.33 kg	Thermal Conductivity	EN12664	0,14 W/mK
m2		Thermal Resistance R-Value	2	.08 (m2K/W)
Area per package / per	2.06 m ² / 123.6 m ²	Biological Durability	EN350-2	Class 1
pallet		CARB2		Compliant
Grading	Calm	Slip resistance	CEN/TS15676	NPD
Joint	Tongue & Groove			
Installation method	Glue-down			
Floor heating	Yes			
Wear leayer material /	Hardwood / 3.5 mm			
thickness				
Core material	Pine			
Hardness (Brinell) value /	3,7 / 2.2 - 5.9			
range				
Warranty	30 years			

DETAILED DESCRIPTION

Even colour with minor variations. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark.

Small sized knots in limited numbers allowed.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection

