



## OAK PALAZZO ROVERE

Oak Palazzo Rovere is a floor with the strips laid in a Dutch pattern. The floor is supplied in finished boards and installed in the same simple way as Kährs' other multi layer parquet flooring. A certain amount of attention must be paid to the pattern when laying the floor.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	153138EK50KW240 / 7393969024150
Design / Wood Species	Dutch pattern / Oak
Surface Treatment /	Satin lacquer / Natural
Natural/Stained	
Width x Length x Thickness	198.5 x 2426 x 15 mm
Weight per package / per	23 kg / 7.93 kg
m2	
Area per package / per	2.9 m <sup>2</sup> / 130 m <sup>2</sup>
pallet	
Grading	Variation
Joint	Woodloc® 5S
Installation method	Glue-down, Floating
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce lamella
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	
LRV / LRV Std1 / LRV Std2	34 / 3.9 / 7.8

PRODU	JCT I	DETAI	LS
-------	-------	-------	----

Warranty	30 years	
- TECHNICAL PROPERTIES	;	
- Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
- kg/m³		
- Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
- Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
- CARB2		Compliant
- Slip resistance	CEN/TS15676	NPD







## DETAILED DESCRIPTION


Even colour with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.

**Colour change**: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

## Other products in this collection







OAK PALAZZO BIANCO



OAK PALAZZO FUMO



OAK PALAZZO ROVERE