



OAK PALAZZO ROVERE

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153138EK50KW240	Wood Species	White Oak	Moisture	EN13183	7%±2%
EAN Code	7393969024150	Design	Pattern	content		
Surface Treatment	Silk matte finish	Grading	Variation	Minimun Mean Density kg/m³ >500 kg/m³		
Dimensions	7 7/8 x 95 1/2 "	Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	50.7 lbs	Collection	European Renaissance Collection	Formaldehyde	EN717-1	E1
Area per Package	31.2 sqft			Emission		
Area per pallet	1399.3 sqft	Resandable	2 times	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.	Natural/Stained	Natural	Breaking	EN1533	NPD
		Brinell Value	3,7	Strength N/mm ²		
		Joint	Woodloc® 5S			
DETAIL DESCRIPTION		Floor heating	Yes	 Thermal Conductivity 	EN12664	0,14 W/mK
Even colour with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.		Warranty	30 years	Thermal Resistance R-Value .		.11 (m2K/W)
		Warranty	25 years	Biological	EN350-2	Class 1
COLOR CHANGE		Wear-layer material	Hardwood	Durability		
brown.		Wear Layer Thickness	1/8"	CARB2		Compliant
		Core material	Pine/Spruce lamella	Slipperiness CEN/TS15676		NPD
		Thickness	5/8"			
		Installation method	Glue-Down, Floating			
		LRV	34			

Other products in this collection







Oak Palazzo Bianco

Oak Palazzo Fumo

Oak Palazzo Rovere

CERTIFICATES











Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.