



OAK MANOR

The powdery white stain on this single-strip oak floor from the Grande Collection softens its rustic expression and allows the blonde tones of the wood to come through. Each board is meticulously hand-scraped, which enhances the worn appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. This product must be oiled after installation and prior to use.

PRODUCT DETAILS Product type / Construction Wood Floors / 3-layer parquet Article Number / EAN Code 201XABEKFVKE280 / 7393969031523 Plank / Oak Design / Wood Species Surface treatment / Oil / Stained Natural/Stained Bevelled 4-sided, Brushed, Handscraped Design features Width x Length x Thickness 260 x 2800 x 20 mm Weight per package / per 38 kg / 13.1 kg m2 Area per package / per 2.91 m² / 81.48 m² pallet Grading Variation Joint Tongue & Groove Installation method Glue-down Floor heating Nο Wear leayer material / Hardwood / 5 mm thickness Resandable 2-4 times Backside material Veneer Warranty 30 years

TECHNICAL PROPERTIES

| Moisture content | EN13183 | 7%+2% |
|----------------------------|-------------|-------------|
| Worsture content | LINIDIOD | 7 70 1 2 70 |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,125 W/mK |
| Thermal Resistance R-Value | ! | .16 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |









DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

