



MANOR OAK

A rustic, white washed and hand scraped product, may contain knots and cracks. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	201XABEKFVKE280	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969031523	Design	1-strip	Minimum Mean Density kg/m³		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Variation	Reaction To Fire	EN13501-1	Dfl-s1
Refining Treatment	Bevelled 4-sided, Brushed, Handscraped	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1
Dimensions	260 x 2800 mm	Collection	Grande Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	38 kg	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area per Package	2.9 m²	Joint	Tongue & Groove	Thermal Conductivity	EN12664	0,125 W/mK
Package info	Packages may contain start and stop boards.	Floor heating	No	Thermal Resistance R-Value		.16 (m2K/W)
DETAIL DESCRIPTION		Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1
		Wear Layer Thickness	5 mm	CARB2		Compliant
		Backside material	Veneer	Slipperiness	CEN/TS15676	NPD
			20 mm			
		Installation method	Glue-down			
		Surface Colour	White			

COLOUR CHANGE

Stained product - noticable color change over time.



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.