



# OAK PORTOFINO

This 2-strip oak floor from the Sand Collection features subtle grain and colour variations. The white finish creates a seamless expression with soft sable hues. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

## PRODUCT DETAILS

|   |   |
|---|---|
| <b>Article Number</b>                   | 152N38EKOVKW 0                              |
| <b>EAN Code</b>                         | 7393969026987                               |
| <b>Surface treatment</b>                | Matt lacquer                                |
| <b>Dimensions</b>                       | 2423 x 200 x 15 mm                          |
| <b>Weight per Package (kg)</b>          | 23.00 kg                                    |
| <b>Area per Package (m<sup>2</sup>)</b> | 2.90 m <sup>2</sup>                         |
| <b>Area per pallet (m<sup>2</sup>)</b>  | 130.10 m <sup>2</sup>                       |
| <b>Package info</b>                     | Packages may contain start and stop boards. |

## DETAIL DESCRIPTION

Naturally occurring wood colour variations allowed, from light to dark brown. Will include sapwood. The product includes medium sound and black knots. Knots may vary in size and numbers.

## COLOUR CHANGE

Stained product - noticeable color change over time.

## FACTS

|                             |                     |
|-----------------------------|---------------------|
| <b>Wood Species</b>         | Oak                 |
| <b>Board</b>                | 2-strip             |
| <b>Grading</b>              | Variation           |
| <b>Range</b>                | Kährs Original      |
| <b>Collection</b>           | Sand Collection     |
| <b>Resandable</b>           | 2-3 times           |
| <b>Natural/Stained</b>      | Stained             |
| <b>Brinell Value</b>        | 3,7                 |
| <b>Joint</b>                | Woodloc® 5S         |
| <b>Floor heating</b>        | Yes                 |
| <b>Warranty</b>             | 30 years            |
| <b>Wear-layer material</b>  | Hardwood            |
| <b>Wear-layer thickness</b> | 3.5 mm              |
| <b>Core material</b>        | Pine/Spruce lamella |
| <b>Thickness</b>            | 15 mm               |
| <b>Surface Colour</b>       | White E0V/EFV       |
| <b>Installation method</b>  | Floating, Glue-down |

## TECHNICAL PROPERTIES

|  |                          |                          |
|--|--------------------------|--------------------------|
| <b>Moisture content</b>                      | EN13183                  | 7%±2%                    |
| <b>Minimum Mean Density kg/m<sup>3</sup></b> | >500 kg/m <sup>3</sup>   |                          |
| <b>Reaction To Fire</b>                      | EN13501-1                | Dfl-s1                   |
| <b>Formaldehyde Emission</b>                 | EN717-1                  | E1                       |
| <b>Content PCP</b>                           | CEN/TR14823              | ≤ 5 x 10 <sup>-6</sup> n |
| <b>Breaking Strength N/mm<sup>2</sup></b>    | EN1533                   | NPD                      |
| <b>Thermal Conductivity</b>                  | EN12664                  | 0,14 W/mK                |
| <b>Thermal Resistance R-Value</b>            | .11 (m <sup>2</sup> K/W) |                          |
| <b>Biological Durability</b>                 | EN350-2                  | Class 1                  |
| <b>CARB2</b>                                 | Compliant                |                          |



**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*