



Scandinavian Naturals Collection



# BEECH VIBORG

Scandinavian Beech, three strip design, silk matte finish, some knots.

## PRODUCT DETAILS

|                                     |                                    |
|-------------------------------------|------------------------------------|
| Product type / Construction         | Wood Flooring / 3-layer engineered |
| Article Number / EAN Code           | 153N18BK50KW240 / 7393969020121    |
| Design / Wood Species               | 3-strip / Beech                    |
| Surface Treatment / Natural/Stained | Silk matte finish / Natural        |
| Width x Length x Thickness          | 7 7/8 x 95 3/8 x 5/8"              |
| Weight per package / per m2         | 50.7 lbs / 17.5 lbs                |
| Area per package / per pallet       | 31.2 sqft / 1400.4 sqft            |
| Grading                             | Variation                          |
| Joint                               | Woodloc® 5S                        |
| Installation method                 | Floating, Glue-Down                |
| Floor heating                       | No                                 |
| Wear leayer material / thickness    | Hardwood / 1/8"                    |
| Resandable                          | 2 times                            |
| Core material                       | Pine/Spruce lamella                |
| Hardness (Brinell) value / range    | 3,8 / 2.0 - 5.9                    |
| Warranty                            | 25 years                           |

## TECHNICAL PROPERTIES

|                                     |             |                        |
|-------------------------------------|-------------|------------------------|
| Moisture content                    | EN13183     | 7%±2%                  |
| Minimun Mean Density                |             | >500 kg/m <sup>3</sup> |
| Reaction To Fire                    | EN13501-1   | Dfl-s1                 |
| Formaldehyde Emission               | EN717-1     | E1                     |
| Content PCP                         | CEN/TR14823 | ≤ 5 x 10-6n            |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD                    |
| Thermal Resistance R-Value          |             | .11 (m2K/W)            |
| Biological Durability               | EN350-2     | Class 1                |
| CARB2                               |             | Compliant              |
| Slip resistance                     | CEN/TS15676 | NPD                    |



## DETAILED DESCRIPTION

Even light colour with minor variations.  
Small sized knots in limited numbers allowed.

**Colour change:** Changes from pink/tan tones to amber.  
Packages may contain start and stop boards.

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



Beech Viborg



Ash Gotland