

## **BEECH VIBORG**

Scandinavian Beech, three strip design, silk matte finish, some knots.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153N18BK50KW240	Wood Species	Beech	Moisture	EN13183	7%±2%
EAN Code	7393969020121	Design	3-strip	content		
Surface Treatment	Silk matte finish	Grading	Variation	Minimun Mean Density kg/m <sup>3</sup> >500 kg/m <sup>3</sup>		
Dimensions	7 7/8 x 95 3/8 "	Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package Area per Package	50.7 lbs 31.2 sqft	Collection	Scandinavian Naturals Collection	Formaldehyde Emission	EN717-1	E1
Package info	Packages may contain start and stop boards.	Resandable	2 times	Content PCP	CEN/TR14823	≤ 5 x 10-6n
		Natural/Stained	Natural	Breaking	EN1533	NPD
		Brinell Value	3,8	Strength		
DETAIL DESCRIPTION		Joint	Woodloc® 5S	N/mm <sup>2</sup>		
Even light colour with minor variations. Small sized knots in limited numbers allowed.		Floor heating	No	<ul> <li>Thermal</li> <li>Conductivity</li> </ul>	EN12664	0,14 W/mK
		Warranty	30 years	Thermal Resistance R-Value		.11 (m2K/W)
COLOR CHANGE		Warranty	25 years	Biological	EN350-2	Class 1
Changes from pink/tan tones to amber.		Wear-layer material	Hardwood	Durability		
		Wear Layer Thickness	1/8"	CARB2		Compliant
		Core material	Pine/Spruce lamella	Slipperiness CEN/TS15676		NPD
		Thickness	5/8"			
		Installation method	Floating, Glue-Down			

## Other products in this collection



**Beech Viborg** 

Ash Gotland

## CERTIFICATES



## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.